


Solar Cable Connector

PV-BN101A Solar Connector



IEC 1500V
UL 1500V



UL: 6703
IEC: 62852



-40℃~85℃



UL94-V0



IP 68



UV Resistance




Product Overview

PV-BN101A connectors use high quality materials that guarantee long-term reliability. Lower contact resistance and higher current transfer capability ensure high product efficiency. PV-BN101A connectors have IP68 water-proof rating and can be used in a wide operating temperature range from -40 °C to 85°C.

Technical Data

Rated Voltage	IEC 1500V\UL1500V
Certification	IEC 62852; UL 6703
Rated Current	35A/40A
Ambient temperature	-40℃ up to +85℃
Contact Resistance	≤0.25mΩ
Pollution Degree	Class II
Protection Degree	Class II
Fire Resistance	UL94-V0
Rated Impulse Voltage	16KV
Locking System	NEC Locking Type





Order Data

Part No.	Cable OD Range/mm	Cable Cross Section	Standard Package Unit	Description
PV-BN101A-F1	4.7mm~6.0mm	2.5mm ² /4mm ² 14AWG/12AWG	500 pairs / Carton	Full Pairs
PV-BN101A-F1-MH			500 pcs / package	F2 Male Housing
PV-BN101A-F1-FH			500 pcs / package	F2 Female Housing
PV-BN101A-MT			500 pcs / package or 2500 pcs / Reel	Male terminal
PV-BN101A-FT			500 pcs / package or 2500 pcs / Reel	Female terminal
PV-BN101A-F2	5.6mm~6.9mm	4mm ² /6mm ² 12AWG/10AWG	500 pairs / Carton	Full Pairs
PV-BN101A-F2-MH			500 pcs / package	F2 Male Housing
PV-BN101A-F2-FH			500 pcs / package	F2 Female Housing
PV-BN101A-MT			500 pcs / package or 2500 pcs / Reel	Male terminal
PV-BN101A-FT			500 pcs / package or 2500 pcs / Reel	Female terminal
PV-BN101A-F6	6.9mm~8.7mm	10mm ² 8AWG	500 pairs / Carton	Full Pairs
PV-BN101A-F6-MH			500 pcs / package	F6 Male Housing
PV-BN101A-F6-FH			500 pcs / package	F6 Female Housing
PV-BN101A-MT			500 pcs / package or 2500 pcs / Reel	Male terminal
PV-BN101A-FT			500 pcs / package or 2500 pcs / Reel	Female terminal

Solar Cable Connector

PV-BN101A Solar Connector



How to Order solar cable connector (please choose one code per position, below)

SCC-	X-	X	X	X	
-------------	-----------	----------	----------	----------	--

SCC	Cable Cross Section	Cable OD	Terminals Package	MPQ Housing Package	Variations
Solar Cable Connector	☐ 2.5m²(14Awg)	☐ F1: 4.7~6.0mm	☐ R: Roll	☐ 500 pairs/package	☐ _____
	☐ 4-6mm²(12Awg-10AWG)	☐ F2: 5.6~6.9mm	☐ P: Bulk	☐ 50 pairs/package	
	☐ 10mm²(8Awg)	☐ F6: 6.9~8.5mm	☐ _____	☐ 5 pairs/package	
	☐ _____	☐ _____		☐ 1 pairs/package	
				☐ _____	

* Customized options available

Example:

SCC-6mm-F2-B-500 means the Solar cable connector will match 6mm2 cable with 5.6~6.9 OD. The terminals will be packaged with plastic housing together. 500 plastic housing will be packaged in one package.

Standard Package Info:



Carton Dimension (cm)	Pack list	QTY	Gross Weight (kg)
59cm X 39cm X 20cm	Male Housing	500 pcs	15kg
	Female Housing	500 pcs	
	Male terminal	500 pcs	
	Female terminal	500 pcs	
Remark:500 pairs in one carton package			